



Features

Safety Sealed Packaging (XS-XL) 100 Gloves/Box, 10 Boxes/Case

- Natural Color
- General Purpose Latex Gloves
- Ambidextrous and Powder-Free
- Exceptional strength and durability
- Superior puncture resistance
- Comfortable and silky textured finished
- Perfect for janitorial work, electronic assembly, manufacturing and aeronautics.
- Dated Lot Codes for quality assurance and traceability

Handplus® Latex Manufacturing Standards

*Brand new state-of-the-art manufacturing plant with computer-controlled market leading technology

| Defect | Inspection Level | AQL |
|---|------------------|-----|
| Pinholes (FDA 1000 ml watertight test) | G1 | 2.5 |
| Visual Defects (Major) | G1 | 2.5 |
| Visual Defects (Minor) | G1 | 4.0 |
| Dimensions | S-2 | 4.0 |

Handplus® Latex Gloves

| Size | Reorder# |
|---------|----------|
| X-Small | 060-5 |
| Small | 060-6 |
| Medium | 060-7 |
| Large | 060-8 |
| X-Large | 060-9 |

All specifications are subject to change without notice.

Specification (mm)

| Size | Glove Length | Palm Width | Cuff Thickness | Palm Thickness | Finger Thickness |
|---------|--------------|------------|----------------|----------------|------------------|
| Small | 240 | 85 | 0.09 | 0.10 | 0.13 |
| Medium | 240 | 95 | 0.09 | 0.10 | 0.13 |
| Large | 240 | 105 | 0.09 | 0.10 | 0.13 |
| X-Large | 240 | 115 | 0.09 | 0.10 | 0.13 |

Quality Standards

Testing Methods

- ISO 9002 Certified Manufacturing
- SO13485 Quality Management Systems
- Meets USDA Requirements for food handling

Physical Properties

| Property | ASTM Minimum | Handplus® Latex |
|----------------|--------------|-----------------|
| | Before Aging | Before Aging |
| Tensile (MPa) | 18 | 18 |
| Elongation (%) | 650 | 650 |
| | After Aging | After Aging |
| Tensile (MPa) | 14 | 14 |
| Elongation (%) | 500 | 600 |